

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

## VEHICLE AIRBAG SYSTEM

Kurt HAEUSLMEIER

German

Spilhofstr. 7

D-81927 Muenchen

GERMANY

**Gisela DIEPOLD**

German

Am Rinnerhof 9

D-82205 Gilching

GERMANY

**CROWELL & MORING, L.L.P.**

Washington, D.C. 20044-4300

Telephone No.: (202) 624-2500

Facsimile No.: (202) 628-8844

## VEHICLE AIRBAG SYSTEM

### BACKGROUND AND SUMMARY OF THE INVENTION

[0001] This application claims the priority of German Patent Document DE 101 02 646.3, filed January 20, 2001, the disclosure of which is expressly incorporated by reference herein.

[0002] The invention relates to an airbag system for motor vehicles. The airbag system has an airbag and a deployment arrangement, which fills the airbag with gas when an event occurs that can be interpreted as an impact against an obstacle. The deployment arrangement includes two independently-deployable chambers, each of which is capable of filling the airbag. The first chamber may fill the airbag more fully than the second chamber. After the first chamber has been deployed, the second chamber is deployed with a time delay.

[0003] Airbag systems have become standard equipment for protecting motor-vehicle passengers in accidents. An acceleration sensor provided on the vehicle frame usually detects whether an abrupt deceleration of the vehicle is to be interpreted as an impact against an obstacle. In such a case, a folded-up airbag is filled with gas in fractions of a second through the deployment or ignition of a propellant charge in order to catch the passenger's body and thus protect it against sustained injuries.

[0004] Airbag systems of this type have performed well in practice. Vehicles of the upper-middle class, however, are already being provided with dual-stage

airbag systems, in which the deployment arrangement comprises two chambers that contain an unequal distribution of the respective propellant charge. Conventionally, the propellant chamber with the larger quantity of propellant charge (e.g., 70%) is deployed first. After a delay, the chamber having the correspondingly smaller quantity of propellant charge (e.g., 30%) is deployed. It is known to make the time delay variable, notably as a function of the severity of the accident or crash as detected and assessed by appropriate sensors (EP 0 950 582 A2).

[0005] It has been seen that, for particular accident situations, these conventional airbag systems cannot ensure the optimum protection of the passengers in the involved vehicle. The passenger may be subjected to significant stress, especially a passenger in the so-called OOP (out-of-position) situation, in which his position differs from that of an average or standard passenger. In the OOP situation, the passenger is typically too close to the airbag system, for example due to a braking action that has occurred prior to the crash or impact. Non-belted children seated in the passenger seat are particularly at risk. They may be located directly in the expansion space of the passenger airbag. To offer protection to those passengers in the OOP situation in the event of an impact, it has already been proposed to place less propellant charge in the first chamber than in the second chamber (DE 195 51 0980.A1, EP 0 958 974 A2). This, however, is a drawback for a passenger in the average or standard position.

[0006] In view of this, it is the object of the present invention to disclose an airbag system that functions optimally for the affected passenger in any accident situation.

[0007] The invention uses sensors to detect numerous person-specific variables, especially accident-specific variables, such as the sitting position, weight, size, the locked position of the safety belt, etc. Typical accident-specific variables include the actual vehicle speed and the vehicle speed relative to a vehicle traveling in front of it, as well as the nature of the crash.

[0008] With these sensors, it is possible to implement the reversible ignition sequence of the propellant charges of the two chambers in accordance with the invention.

[0009] Other objects, advantages and novel features of the present invention will become apparent from the following detailed description of the invention when considered in conjunction with the accompanying drawing.

#### BRIEF DESCRIPTION OF THE DRAWING

[0010] Figure 1 is a schematic diagram showing the deployment arrangement of an airbag system of the present invention.

#### DETAILED DESCRIPTION OF THE DRAWING

[0011] The invention is described in detail below by way of the exemplary embodiment illustrated in the single drawing figure.

[0012] Figure 1 schematically shows the deployment arrangement 2 of an airbag system 1. The airbag system 1 conventionally has a folded airbag, not

Figure 1 consists of 15 small diagrams arranged vertically, illustrating the stages of chick development. The diagrams are labeled with numbers 1 through 15. The stages show the progression from a single cell (1) to a fully formed chick with a beak and legs (15). The diagrams are arranged in a vertical column and labeled with numbers 1 through 15.

- 4 -

represents the transmission of the ignition signals to the ignition elements 7 and 8. Dashed lines 14 show that further restraining systems such as belt tighteners, side airbags and the like can also be actuated in the same manner by the deployment control device 11 in the illustrated scenario.

[0015] The vehicle contains further sensors (not shown in detail) that detect variables associated with the passenger or the seats. One of such variables, for example, is the seat setting that is indicative of the sitting position and therefore the type of person. In other words, they detect whether the passenger is large or small. The sensors further detect a weight signal, i.e., whether the person is heavy or lightweight, and particularly whether a person is occupying the seat, and other such person-specific variables. A corresponding signal 15 is essentially transmitted to the deployment control device 11.

[0016] It is also advantageous to detect accident-specific variables. For example, the deployment control device 11 can be supplied with a signal 16 that indicates the crash angle, that is, the direction of the primary component of the force acting in an impact. This direction deviates from a specified axis, generally the longitudinal axis of the vehicle. It is further advantageous to detect the actual speed of the vehicle, the vehicle speed relative to an object located in front of the vehicle, typically another vehicle traveling ahead of the vehicle, and to transmit corresponding signals to the deployment control device 11. The deployment control device 11 is also supplied with specific variables relating to the vehicle type, or it permanently stores these variables, as indicated by a type signal 17. The accident-specific and person-specific variables supplied to the

deployment control device 11 are evaluated in terms of the vehicle type in the deployment control device 11. Based on this evaluation, it is not only possible to select a variable time delay between the ignition of the two ignition elements 7 and 8, as is already known per se, but it can also be determined whether a particular accident situation is occurring in which it would be more practical to deploy the airbag containing the smaller quantity of gas first, then fill it with the larger quantity of gas following a delay. In the illustrated case, the corresponding signals are transmitted to the ignition elements 7 and 8 in reverse order, so the propellant charge in the second chamber 6 is ignited first. The larger quantity of propellant charge in the first chamber 5 is ignited after a corresponding delay.

[0017] The variable ignition sequence for the chambers 5 and 6 of the dual-stage deployment unit 4 allows the stress values of the passenger, which are adapted to the respective accident situation, to be reduced to more favorable values. This is especially crucial for the OOP situation. Furthermore, there are more possible degrees of freedom in optimizing the deployment of the airbag, notably with respect to an adaptation to any accident situations that may arise.

[0018] As of the year 2003, the FMVSS 208 regulation will stipulate tests for the OOP situation for the driver and passenger sides, especially for US vehicles.

[0019] The foregoing disclosure has been set forth merely to illustrate the invention and is not intended to be limiting. Since modifications of the disclosed embodiments incorporating the spirit and substance of the invention may occur



to persons skilled in the art, the invention should be construed to include everything within the scope of the appended claims and equivalents thereof.

[illegible]